## **GENERAL MOTORS CORPORATION**

EXECUTIVE ORDER A-006-1576-1 New On-Road Heavy-Duty Engines Page 1 of 1 Pages

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

| MODEL<br>YEAR  | MODEL ENGINE FAMILY 2009 9GMXE06.0584  |   | ENGINE<br>SIZES (L)   | FUEL TYPE  | STANDARDS<br>& TEST  | SERVICE  | ECS & SPECIAL FEATURES 3  | DIAGNOSTIC <sup>8</sup> EMD  |  |  |  |
|--|--|---|---|--|--|--|---|--|--|--|--|
|  |  |   | 6.0   | Gasoline   | Otto   | CLASS THOO   | 2TWC, 2HO2S(2), SFI   |  |  |  |  |
| 1  | ENGINE'S IDLE<br>NS CONTROL  |   |   | ADDI   | TIONAL IDLE EM   | ISSIONS CON  | ITROL <sup>5</sup>  |  |  |  |  |
|  | N/A  |   | N/A   |  |  |  |   |  |  |  |  |
| ENGINE (I  | L)   | ENGINE MODELS / CODES (rated power, in hp)  |   |  |  |  |   |  |  |  |  |
| 6.0  |  | LY6 / 40 (323), 60 (307), 80 (322)  |   |  |  |  |   |  |  |  |  |
| L=lifer; hp=<br>CNG/LN<br>L/M/H H<br>ECS=en<br>up catalyst;<br>TBI=throttle<br>super charg<br>control mod<br>ESS=en<br>(per 13 CCf | -horsepower; kw=ki<br>MG=compressed/liqu<br>IDD=light/medium/he<br>nission control syste<br>DPF=diesel particu<br>body fuel injection:<br>per; CAC=charge ain<br>ule; EM=engine mo<br>gine shutdown syste<br>R 1956.(a)(6)(D); E | lowatt; his<br>efied nature<br>m; TWC/<br>late filter;<br>SFI/MFI=<br>cooler; Edification;<br>em (per 13<br>xempt=e | =hour;<br>ral gas; LPG=liquef<br>y-duty diesel; UB=u<br>DC=three-way/oxidiz<br>PTOX=periodic trap<br>sequential/multi port<br>EGR / EGR-C=exhau<br>2 (prefix)=parallel;<br>0 CCR 1956.8(a)(6),<br>xempted per 13 CCF, | ed petroleum gas; E85=85% elh rhan bus; HDD=heavy duty Otto; ing catalyst; NAC=NOx adsorptii oxidizer; HO25/O25=heated/ox; fuel injection; DGI=drivert gasolir st gas recirculation / cooled EGR (2) (suffix)=in series; 3(1); 30g=30 g/hr NOx (per 13 C | and fuel; MF=multion catalyst; SCR-U /gen sensor; HAF5 e injection; GCAR : PAIR/AIR=pulsed CR 1956.8(a)(6)(C fuel systems; N/A | fuel a.k.a. BF= / SCR-N=select /AFS=heated/a B=gaseous cart /secondary air i ); APS =interna =not applicable | R 86.abc=Title 40, Code of Federal Regulation  =bi fuel; DF=dual fuel; FF=flexible fuel;  tive catalytic reduction – urea / ammonia;  tir-fuel-ratio sensor (a.k.a., universal or linear  suretor; IDI/DDI=indirect/direct diesel injection;  plection; SPL=smoke puff limiter; ECM/PCI  til combustion auxiliary power system; ALT=:  (e.g., Otto engines and vehicles); | WU (prefix) =warm-<br>oxygen sensor):<br>nr; TG/SC=turbo/<br>M=engine/powertrain |  |  |  |

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

| in<br>g/bhp-hr | NMHC |      | NOx  |      | NMHC+NOx |      | co   |      | PM   |      | нсно  |      |
|----------------|------|------|------|------|----------|------|------|------|------|------|-------|------|
|                | FTP  | EURO | FTP  | EURO | FTP      | EURO | FTP  | EURO | FTP  | EURO | FTP   | EURO |
| STD            | 0.14 | *    | *    | *    | *        | *    | 14.4 | *    | 0.01 | *    | 0.01  | *    |
| FEL            | *    | *    | 0.70 | *    | *        | *    | *    | *    | *    | +    | *     | *    |
| CERT           | 0.08 | *    | 0.49 | *    | *        | *    | 6.6  | *    | .*   | *    | 0.001 | *    |
| NTE            | +    |      | *    |      | •        |      | *    |      | *    |      | •     |      |

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

**BE IT FURTHER RESOLVED:** Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

**BE IT FURTHER RESOLVED:** For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1576 dated May 20, 2008.

Executed at El Monte, California on this \_\_\_\_\_\_ day of June 2008.

Raphoul Sannows

**Mobile Source Operations Division**